

INSERT YOUR LOGO HERE	COMPANY Safety Management System	Doc No:	LADDERS
		Initial Issue Date:	Insert Date
LADDER SAFETY	Usually one year from issue date	Revision Date:	Initial Version
		Revision No.:	0
		Next Review Date:	Insert Date
Preparation: Safety Mgr	Authority: President	Issuing Dept: Safety	Page: Page 1 of 4

Purpose

The purpose of the program is to prescribe rules and establish minimum requirements for the construction, care, and use of the common types of ladders.

All ladders that are purchased and placed into service; or, any ladders that are engineered, manufactured and installed on any COMPANY equipment shall follow the requirements set forth by this program.

Scope

This program is applicable to all employees who may utilize ladders. When work is performed on a non-owned or operated site, the operator's program shall take precedence, however, this document covers COMPANY employees and contractors and shall be used on owned premises. or when an operator's program doesn't exist or is less stringent.



- Notice that our name is not anywhere on the document
- You can delete or change the header and footer
- You can use your own template and cut/paste the body

Definitions

Ladder - an appliance usually consisting of two side rails joined at regular intervals by cross- pieces called steps, rungs, or cleats, on which a person may step in ascending or descending.

Stepladder - a self-supporting portable ladder, nonadjustable in length, having flat steps and a hinged back. Its size is designated by the overall length of the ladder measured along the front edge of the side rails.

Single ladder - a non-self-supporting portable ladder, nonadjustable in length, consisting of but one section. The overall length of the side rail designates its size.

Extension ladder - a non-self-supporting portable ladder adjustable in length. It consists of two or more sections traveling in guides or brackets so arranged as to permit length adjustment. Its size is designated by the sum of the lengths of the sections measured along the side rails.

Fixed ladder - a ladder permanently attached to a structure, building, or equipment.

Individual-rung ladder - a fixed ladder each rung of which is individually attached to a structure, building, or equipment.

Cage - a guard that may be referred to as a cage or basket guard, which is an enclosure that is fastened to the side rails of the fixed ladder or to the structure to encircle the climbing space of the ladder for the safety of the person who must climb the ladder.

Key Responsibilities

Managers and Supervisors

- Managers and supervisors are responsible for ensuring that all employees, and/or contractors have been trained in the use and inspection of ladders in accordance to the manufactures guidelines.

INSERT YOUR LOGO HERE	COMPANY Safety Management System	Doc No:	LADDERS
		Initial Issue Date:	Insert Date
LADDER SAFETY		Revision Date:	Initial Version
		Revision No.:	0
		Next Review Date:	Insert Date
Preparation: Safety Mgr	Authority: President	Issuing Dept: Safety	Page: Page 2 of 4



- Managers and supervisors are responsible for ensuring that all employees and contractors are aware that if an inspection discovers a defect, the ladder shall not be used and taken out of service.

Employees


- Employees shall inspect ladders prior, during and at the completion of each use to ensure the condition of the ladder and the safety of its occupants.
- Employees are responsible for following this program and reporting any damage or repairs that may be needed to their supervisor.


Procedure

Inspection, Care and Safe Work Practices of Ladders

Downloads immediately as a Word file that is easily customized to your company information





Save time!

We'll customize your safety program with your company name, logo and upload with answers to ISNetworld®, PICS, PEC/Premier, Browz or CanQual within 24 hours.

[Click here for more information.](#)

Documents purchased from this website are the intellectual property of Safety Resourcing LLC and are solely for use and modification by the individual purchasing company and are not to be used for resale, distribution, republication nor any profit generating use without prior written permission by Safety Resourcing LLC and are covered by copyright protection.

not be used; improvised repairs shall not be made.

- All wood parts shall be free from sharp edges and splinters; sound and free from accepted visual inspection from shake, or other irregularities.

Care

Ladders shall be maintained in good condition at all times, the joint between the steps and side rails shall be tight, all hardware and fittings securely attached, and the movable parts shall operate freely without binding or undue play.

Metal bearings of locks, wheels, pulleys, etc., shall be frequently lubricated.

Frayed or badly worn rope shall be replaced. Safety feet and other auxiliary equipment shall be kept in good condition to ensure proper performance.

Rungs shall be kept free of grease and oil.

Ladders shall be stored in a well-ventilated area in a manner to prevent sagging and warping.

INSERT YOUR LOGO HERE	COMPANY Safety Management System		Doc No:	LADDERS
			Initial Issue Date:	Insert Date
			Revision Date:	Initial Version
LADDER SAFETY			Revision No.:	0
			Next Review Date:	Insert Date
Preparation: Safety Mgr	Authority: President	Issuing Dept: Safety	Page:	Page 3 of 4

Ladder Safe Work Practices

Ladders shall be used only for the intended purpose for which they were designed.

The ladder shall be secured at the top or held by another person at the base.



The footing of the ladder shall be placed on a stable and level surface.

Extension ladders shall be placed at a 4:1 ratio. Ladders shall be used at an angle such that the horizontal distance from the top support to the foot of the ladder is approximately one-quarter of the working length of the ladder (the distance along the ladder between the foot and the top support).


When ladders are not able to be extended then the ladder shall be secured at its top to a rigid support that will not deflect.


Ladders shall not be placed on boxes, barrels, or other unstable bases to obtain additional height.

Ladders shall not be used in a horizontal position as platforms, runways, or scaffolds.

Downloads immediately as a Word file that is easily customized to your company information





Save time!
We'll customize your safety program with your company name, logo and upload with answers to ISNetworld®, PICS, PEC/Premier, Browz or CanQual within 24 hours.
[Click here for more information.](#)

Documents purchased from this website are the intellectual property of Safety Resourcing LLC and are solely for use and modification by the individual purchasing company and are not to be used for resale, distribution, republication nor any profit generating use without prior written permission by Safety Resourcing LLC and are covered by copyright protection.

Up to and including 36'	3
Over 36 up to and including 48'	4
Over 48 up to and including 60'	5

Ladders shall extend a minimum of 3 feet above top of upper landing surface. The ladder side rails shall extend at least 3 feet (.9m) above the upper landing surface. When ladders are not able to be extended then the ladder shall be secured at its top to a rigid support that will not deflect.

The employee shall maintain a three (3)-point grip on the ladder at all times and carry tools/equipment on a belt or hoist up. Do not carry anything in the hands that could cause injury in case of fall.

The employee shall face the ladder while ascending or descending.

The bracing on the back legs of stepladders is designed solely for increasing stability and not for climbing.



INSERT YOUR LOGO HERE	COMPANY Safety Management System		Doc No:	LADDERS
			Initial Issue Date:	Insert Date
			Revision Date:	Initial Version
LADDER SAFETY			Revision No.:	0
			Next Review Date:	Insert Date
Preparation: Safety Mgr	Authority: President	Issuing Dept: Safety	Page:	Page 4 of 4

The ladder shall not be moved while occupied.


Portable Ladders


Stepladders shall not be longer than 20 feet. Single ladders shall not be longer than 30 feet.

A two-section extension ladders shall not be longer than 60 feet. All ladders of this type shall consist of two sections, one to fit within the side rails of the other, and crossed in such a manner that the upper section can be

Downloads immediately as a Word file that is easily customized to your company information





Save time!

We'll customize your safety program with your company name, logo and upload with answers to ISNetworld®, PICS, PEC/Premier, Browz or CanQual within 24 hours.

[Click here for more information.](#)

- II.(holds 225 lbs)

Documents purchased from this website are the intellectual property of Safety Resourcing LLC and are solely for use and modification by the individual purchasing company and are not to be used for resale, distribution, republication nor any profit generating use without prior written permission by Safety Resourcing LLC and are covered by copyright protection.

Ladders shall be constructed to withstand a minimum of 200 pounds.

All metal rungs shall have a minimum diameter of 3/4 inches and wooden rungs shall have a minimum diameter of 1 1/8 inches.

Rungs shall not be more than 12 inches apart and shall be uniform throughout the length of the ladder.

Rungs shall be a minimum length of 16 inches and provide protection so a foot cannot slip off the end.

Rungs shall have a minimum of 7 inches between itself and the structure behind it.

A fall restraint system must be provided for all fixed ladders greater than six feet in length.

- A Cage is required when the fixed ladder is at least twenty feet tall.
- Cages on fixed ladders shall not begin at a point less than 7 feet nor greater than 8 feet from the walking surface below the cage.
- Cages shall provide a clear width of 15 inches in each direction of the rung's centerline.
- Cages shall not extend less than 27 inches, but not greater than 28 inches from the centerline of the rung.
- A climbing fall restraint system may be substituted for a ladder cage.